RAILWAY

STRANDS FOR ACSR FEEDER CONDUCTOR CORES

With the different types of cores, FGC can meet the needs of the market for ACSR FEEDER.

TECHNICAL FEATURES OF THE MATERIALS

GALVANIZED STEEL STRANDS

Characteristics	Value
Diameters	from 2,85 to 24,00 mm
Tensile strength	> 135 daN/mm^2
Class and mass of coating	A > 215 g/m^2
Heavy zinc coating	> 549 g/m^2
MBL	from 2700 to 57000 daN
Section	from 20,9 to 340 mm^2
Grease (when required)	Type A EN 50326
Standards	CEI 7-2, EN 50189, IEC, ASTM, BS
Certifications	RFI, SNCF

The material is strictly controlled during every stage of manufacturing according to our Quality System in compliance with **EN ISO 9001:2008**

CONSTRUCTIONS

1×7 1×19 1×37

PACKAGING

STANDARD

- Wooden reels from 1000 to 4500 kg
- The strand can be wrapped on metal spools

SEAWORTHY PACKING

- Treated and fumigated wooden reels FAO ISPM 15

FERRIERE GIUSEPPE CIMA SRL
Via Belfiore 17, 23900 LECCO – ITALY | fgc@ferrierecima.it | +39.0341.364632 | www.ferrierecima.it